

FlowCon Actuators Selection Matrix

FlowCon Part no.		FlowCon valve types											
		EVS 15-25mm (1/2"-1")	EVC 15-20mm (1/2"-3/4")	ABM 15-40mm (1/2"-2")	UniQ® 15-20mm (1/2"-3/4")	Green.0/1/2 15-40mm (1/2"-2")	Green.3 40-50mm (1 1/2"-2")	Unimizer® 15-80mm (1/2"-3")	Unimizer® 100-150mm (4"-6")	SM.1/2 15-40mm (1/2"-1 1/2")	SM.3/4/5/6 50-250mm (2"-10")	FIT 65-250mm (2 1/2"-10")	T-JUST 15-25mm (1/2"-1")
Thermal ON/OFF													
24V	EV.0.4	X	X		X								X
	FT.0.4					X							
120V	EV.0.5	X	X		X								
230V	EV.0.3	X	X		X								X
	FT.0.3					X							
Thermal ON/OFF with end switch													
24V	EV.1.4	X	X		X								
230V	EV.1.3	X	X		X								
Thermal modulating													
24V	EV.0.2	X	X		X								
	FT.0.2					X							
Electrical 2-position													
24V	BBTS1000			X				X					
	TT000								X				
	FN.0.4					X							
	FH						X						
	FH.1 w/failsafe						X						
	FN.1.2 w/failsafe					X							
	FN.1.4 w/failsafe				X	X							
	FN.5.4				X								
230V	FN.0.3				X	X							
240V	BBTHV1200A			X				X					
	TT300								X				
Electrical 2-position with end switches													
24V	BBTS1021			X				X					
	TT020								X				
240V	BBTHV1221A			X				X					
	TT320								X				
Electrical 3-point floating													
24V	BBTS1000			X				X					
	TT000								X				
	FN.0.4					X							
	FH						X						
	FN.1.4 w/failsafe				X	X							
	FN.5.4				X								
230V	FN.0.3				X	X							
240V	BBTHV1200A			X				X					
	TT300								X				
Electrical 3-point floating with end switches													
24V	BBTS1021			X				X					
	TT020								X				
240V	BBTHV1221A			X				X					
	TT320								X				
Electrical modulating													
24V	BBMS2000			X				X					
	TM000								X				
Electrical modulating with end switches													
24V	BBMS2021			X				X					
	TM020								X				
Electrical modulating with feed-back signal													
24V 0(2)-10V	FN.0.2					X							
	FH						X						
	FH.1 w/failsafe						X						
	FN.5.2				X								
	FN.1.2 w/failsafe					X							
	FN.6.2 w/failsafe				X								
24V 0(2)-10V, 0(4)-20mA or 3-point floating	SM0001									X			
	SM0003									X	X	X	
24V 0(2)-10V, 0(4)-20mA, 2-position or 3-point floating	SM0004 w/failsafe									X	X	X	
	SM0005 BACnet									X	X	X	
	SM0006 BACnet w/failsafe									X	X	X	
Adaptor ring for thermal actuator													
Color of ring		Black	Grey		Black	Black							Red

Updated 01.2019



A Griswold Controls LLC./FlowCon International Company

www.flowcon.com

DENMARK · DUBAI · USA · CHINA · SINGAPORE