



Certificate number: 2410708 (2)

Issued 11/12/2024

Expires 11/09/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

FlowCon International ApS.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
FlowCon International ApS
Trafikcenter Alle 17
DK-4200 Slagelse
Denmark



KUKreg4

Product Certificate

Appendix to Certificate number: 2410708

The following products belong to this certificate

<p>PRODUCT DESCRIPTION FlowCon T-Just range of thermostatic regulating valves. T-Just thermostatic regulating insert. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) T- JUST insert A15.I A valve housing, DN15 A20.I A valve housing, DN20 A25.I A valve housing, DN25</p>
<p>SIZE: See models.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 10.0 Bar & maximum operating temperature 85°C valve housing max working pressure 25.0 bar max operating temperature 120°C when used together T-Just 10.0 bar applies and 85°C max operating temperature. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.</p>
<p>MARKING Marking T-Just, DN, flow arrow, FlowCon, (H), (D), production year in date clock YY.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes