

## FlowCon Mini By-Pass Unit - commissioning made even easier

The new FlowCon Mini By-Pass will - with a center measurement of only 40mm - fit directly on small FCUs without further adaptation.

The unit is 20mm male threaded suitable for DN15 EuroCone connections and a variety of union end connections is available. Additionally, the unit can be ordered with extended handles if needed in the specific application.

Finally, the new FlowCon Mini By-Pass can be supplied with one or two side options upon request, e.g. for drain and air vent.

All together, the FlowCon Mini By-Pass unit is a compact and smart solution for both consultants, contractors and maintenance people. The FlowCon all-in-one solution is the easiest solution for automatic balancing and temperature control of HVAC applications.

For further information please contact your local FlowCon office or visit [www.flowcon.com](http://www.flowcon.com).

### Technical data:

- 3 way mini By-Pass unit.
- Forged brass housing.
- Nickel plated brass ball valves.
- Can be fitted with optional strainer and drain possibility on supply side.
- Can be fitted with optional FlowCon inserts/-cartridges on return side (Green, EVS, Composite, E-JUST or Stainless Steel).
- Can be fitted with a range of optional actuators on return side (depending on insert/cartridge selection and valve body).
- ISO Sizes: 4 x 20mm (3/4") male fixed end for DN15 EuroCone. Multiple union end connections available.

